PLT-25GF 25 kVA LPG Generator Set

Technical Data Sheet | 50 Hz | Silent (soundproof) type

PRIME
20 kW / 25 kVA
STANDBY 22 kW / 27.5 kVA

PRODUCT OVERVIEW



SILENT TYPE

MAIN SPECIFICATIONS

Model	PLT-25GF	**Fuel**	LPG (propane + butane); dual-fuel LPG/CNG on request
Prime power	20 kW / 25 kVA	**Standby power**	22 kW / 27.5 kVA
Rated voltage	400/230 V	**Phase**	3-phase
Rated current	36 A	**Frequency**	50 Hz (60 Hz available)
Rated speed	1500 rpm	**Power factor**	0.8

GENERATOR SET

Ignition	Electronic	**Cooling**	Water-cooled
Alternator	Brushless with AVR	**Controller**	SmartGen (Deepsea, DEIF, ComAp optional)

LOAD	LPG CONSUMPTION
100% prime	5 kg/h

DIMENSIONS AND WEIGHT

Dimensions (L × W × H)	2200 × 1050 × 1450 mm	**Weight**	1,000 kg

Options: ATS, parallel and synchronisation control, CHP heat recovery, remote monitoring.

Remark: The technical parameters above are for reference only. Actual data may vary depending on specific production conditions.